AQUA MUSLIN

ULTRA PREMIUM SILK EMULSION (INTERIOR)

aqua paints
দেশের রঙে রাঙাই দেশ

PRODUCT DESCRIPTION



Aqua Muslin Ultra Premium Silk Emulsion brings together elegant aesthetics and high-performance protection for premium interior spaces. Formulated with high-quality acrylic emulsion and carefully selected pigments, it creates a rich silky sheen with a smooth and sophisticated finish.

Its advanced formulation provides excellent flexibility, toughness and interior durability, along with superior water resistance and washability for easier maintenance. Enhanced fungal resistance helps keep painted surfaces fresh and protected, making Aqua Muslin an ideal choice for beautiful, durable and refined interior walls.

LEAD FREE | ANTI FUNGAL | ECO FRIENDLY | WASHABLE | SATIN FINISH

PRODUCT INFORMATION

Pack Size



Coverage

FOR INTERIOR
150-170 Sft/Ltr/1 Coat

FOR INTERIOR
75-85 Sft/Ltr/2 Coats

*Depending on Surface



RECOMMENDED SURFACES

Plaster | Concrete | Bricks | Hard Boards | Veneer | Wooden Surface

METHOD OF APPLICATION

1. Clean the surface with a wire brush, wash with water, and dry completely.
2. Apply 1 coat of 100% thinned Aqua Super Sealer-I, dry for 10-12 hours.
3. Apply 2 coats of Aqua Joy Putty at 6-8 hours interval.
4. Apply again 1 coat of 100% thinned Aqua Super Sealer-I, dry for 10-12 hours.
5. Apply 2 coats of Aqua Muslin as finishing coat at 24 hours interval.

Where the substrate is affected by salt deposits or moisture migration, use Aqua Salt Protection Anti-Efflorescence Sealer or Aquaseal Damp Proof Sealer, as appropriate.

AQUA MUSLIN

ULTRA PREMIUM SILK EMULSION (INTERIOR)

aqua paints
দেশের রঙে রাঙাই দেশ

MIXING RATIOS

Roller
Paint : Water = 3:1

Brush
Paint : Water = 2:1

SHADES

Aqua Premium Interior Shade Card

INSTA COLOR **5000+ Shades**
*Currently Available Through Aqua Fandeck

PRODUCT SPECIFICATION

Pigments	Alkali Resistance Pigment with good light fastness
Thinner	Clean Water
pH	8.5 - 9.0
Touch Dry	30 Minutes
Hard Dry	24 Hours (Recoat)
Viscosity	110 ±5 KU @ 30°C
Binder	Special Grade Acrylic Emulsion
Finish	Satin
Durability	5 Years
Pot Life after Thinning	12 Hours Maximum
Heavy Metal Content	Not Detected
Application Method	Brush, Roller
Storage	12 months in a sealed container stored in a cool & dry place

BSTI

CERTIFIED ISO 9001:2015 COMPANY