# AQUA SUPERSTAR

## PREMIUM ACRYLIC INTERIOR EMULSION

aqua paints
দেশের রঙে রাঙাই দেশ

## PRODUCT DESCRIPTION




Aqua Superstar Premium Acrylic Interior Emulsion is a high-quality interior paint designed to give walls a smooth, elegant and long-lasting finish. Formulated with a pure acrylic emulsion, it offers excellent coverage, flow and leveling for a refined appearance.

Its smooth finish helps reduce visible brush marks, while quality fungicides provide added protection against fungal growth. Aqua Superstar dries quickly and is available in a wide range of attractive shades, making it an ideal choice for creating beautiful and comfortable interior spaces.

LEAD FREE | EXCELLENT ADHESION | ANTI FUNGAL | WASHABLE | ECO FRIENDLY

## PRODUCT INFORMATION

### Pack Size




0.91 Liter | 3.64 Liters | 18 Liters

### Coverage

**FOR INTERIOR**
150-170 Sft/Ltr/1 Coat

**FOR INTERIOR**
75-85 Sft/Ltr/2 Coats

*Depending on Surface




## SURFACES

Plaster | Concrete | Bricks | Hard Boards | Veneer | Wooden Surface

## METHOD OF APPLICATION

1. Clean the surface with a wire brush, wash with water, and dry completely.
2. Apply 1 coat of 100% thinned Aqua Super Sealer-I, dry for 10-12 hours.
3. Apply 2 coats of Aqua Joy Putty at 6-8 hours interval. After overnight drying of Putty, sand smooth with emery paper.
4. Apply again 1 coat of 100% thinned Aqua Super Sealer-I, dry for 10-12 hours.
5. Apply 2 coats of Aqua Superstar as finishing coat at 10-12 hours interval.

*Where the substrate is affected by salt deposits or moisture migration, use Aqua Salt Protection Anti-Efflorescence Sealer or Aquaseal Damp Proof Sealer, as appropriate.*

# AQUA SUPERSTAR

## PREMIUM ACRYLIC INTERIOR EMULSION

aqua paints
দেশের রঙে রাঙাই দেশ

## MIXING RATIOS

**Roller**
Paint : Water = 3:1

**Brush**
Paint : Water = 2:1

## SHADES

**Aqua Premium Interior Shade Card**

INSTA COLOR **5000+ Shades**
*Currently Available Through Aqua Fandeck

## PRODUCT SPECIFICATION

| | |
|---|---|
| Pigments | Alkali resistance pigment with good light fastness |
| Thinner | Clean Water |
| pH | 8.5 - 9.0 |
| Touch Dry | 30 Minutes |
| Hard Dry | 10-12 Hours (Recoat) |
| Binder | Special Grade Acrylic Emulsion |
| Finish | Matt |
| Heavy Metal Content | Not Detected |
| Pot Life after Thinning | 12 Hours Maximum |
| Application Method | Brush, Roller |
| Storage | 12 months in a sealed container stored in a cool & dry place |

BSTI

CERTIFIED ISO 9001:2015 COMPANY