

Aqua Paints NATIONAL - Distemper



PRODUCT DESCRIPTION

Aqua Distemper + (Plus) is made especial Type Vinyl Acrylic emulsion for the use on Interior walls and Ceilings. Due to its unique formulation Aqua Distemper + gives the best coverage and smoothness without using putty or sealer.

USES

Interior Walls and ceilings of all types of newly constructed or old masonry surfaces concrete and brick walls. It is particularly recommended for newly constructed walls where early decorations are necessary.

PRODUCT PROPERTIES

Pigments	Alkali resistance pigment
Thinner	Clean water
P H	9.0
Viscosity(2:1)	130+5 KU @30°C. (Sheen Krebs)
Sp. Gr.	1.55±0.05
Binder /Vehicle	Special type Vinyl acetate-acrylic emulsion
Color	White, Aqua Shade Card, Popular Color's Shades in Market & Customer requirement
Durability	1-2 years
Storage	12 months in a sealed container if stored in a cool & dry place
Drying Time	Touch dry : 30 mins Hard dry : 4-6 Hrs Recoating Time : 4-6 Hrs
Application Method	Brush, Roller
Thinning	40-50%
Finish	Matt. Finish
Packages	0.9l Ltr.3.64 Ltr.18.2 Ltr.

Aqua Paints NATIONAL - Distemper

DIRECTION TO USE

Surface preparation: Minimum 3 months time need to dry up the new wall. After drying up clean the loose materials, dusts of wall by stone & sand paper. Then use first coat aqua water sealer. After 4/6 hours drying use 2 coats of aqua wall putty for smooth finish vertically and horizontally 6/8 hour's interval. After 12 hours of using putty clean the wall with emery or sand papers. Apply 2 coats finishing paint in 4/6 hours interval.

In case of old or painted wall then remove all spot or paint by scrapping & also use emery paper for more smoothness. For removing grease or oily substance use washing powder & get it well dried.

For damping wall at first protect the damp & get it dried up. Use bleaching powder or fungus preventive solution with wire brush & get it dried up. Thereafter use aqua water sealer, putty & apply Finish paint.

Application process: 1st chalk wash after 4/6 Hours paint 2 coat (4/6Hours interval).
Get better result - 1st coat sealer putty (2 coats 4/6hours interval) paint 2 coat.

AWARENESS

- Do not mix excess water to put it in using condition.
- Does not use chalk to get good result.
- Mix less water in 2nd coat than that of first coat.
- Do not apply paint if temperature is below 10°C.
- Do not apply paints on watery wall.

SAFETY & HEALTH

- Ensure good ventilation during application.
- If splashes enter eyes wash immediately with plenty of water.
- Prolonged skin contact should be avoided.
- Take normal precautions to avoid inhalation of spray mist.
- Keep away from children.

For more information on our products and services, visit us at www.aquapaints.com

WARNING: IMITATION OF GRAPHICS IS A PUNISHABLE OFFENCE.

Head Office: South Avenue Tower (2nd Floor) House # 50, Road # 3, 7 Gulshan Avenue, Gulshan-1, Dhaka-1212, Bangladesh

Satellite Office: Elite House, 54 Motijheel C/A, (2nd Floor) Dhaka-1000, Bangladesh

Color Factory: Octagon Fibres & Chemicals Ltd. 128 Himerdighi, Tongi I/A Gazipur-1710, Bangladesh

For feedback/complaints, write to the above address or call +88 02 9859998, 9857884, 9561376, 7160132, 9804496

E-mail : info@aquapaints.com

Aqua paints No Added Lead, Mercury, Arsenic & Chromium

Manufactured under license from **Octagon Fibres & Chemicals Ltd.**